



NOTES :

1. THE FOLLOWING INFORMATION IS OBTAINED FROM THE PROJECT DESIGN DRAWINGS:
 - a. POLE LENGTH AND STRENGTH.
 - b. SPECIAL FOUNDATION REQUIREMENTS.
 - c. POLE EMBEDMENT DEPTH.
 - d. PHASE CONDUCTOR AND OVERHEAD EARTHWIRE SIZE.
 - e. VARIATIONS TO STANDARD CROSSARM REQUIREMENTS.
 - f. STAY REQUIREMENTS.
 - g. DEVIATION ANGLE.
 - h. ASSESSED EARTHING REQUIREMENTS.
2. WHEN DESIGNING UNDERBUILT CIRCUITS ON A 33KV STRUCTURE, THE POSSIBLE USE OF LIVE LINE WORKING PROCEDURES MUST BE CONSIDERED WHEN NOMINATING THE CIRCUIT SEPARATION TO ALLOW A MINIMUM CLEARANCE OF 2500mm IF REQUIRED.
3. THE LOAD AND DEVIATION ALLOWABLE ON THE EYEBOLT IS TO BE DETERMINED FROM DRG: 520324.
4. LONGROD INSULATORS TO BE USED UNDER NORMAL CONDITIONS.
5. THE CROSSARM BRACE ATTACHMENT POINT ON A CONCRETE POLE IS TO BE AN M12 STAINLESS STEEL EARTH FERRULE.
6. THE OHEW IS TO BE BONDED TO AN M12 STAINLESS STEEL EARTH FERRULE ON THE CONCRETE POLE.
7. ONLY THE 3000mm STEEL CROSSARM OPTION IS SHOWN ON THIS CONSTRUCTION DRAWING. REFER TO DRG: 237491 FOR DRILLING PATTERN OF ALTERNATE CROSSARM.
8. ONLY THE SINGLE PHASE CONDUCTOR WITH OPGW SPLICE BOX TERMINATION OVERHEAD EARTHWIRE OPTION IS SHOWN ON THIS CONSTRUCTION DRAWING.
9. USE THE OPGW SPLICE BOX TERMINATION ARRANGEMENT WHEN ERECTING AN OPGW OVERHEAD EARTHWIRE. USE THE STANDARD EARTHWIRE TERMINATION ARRANGEMENT WHEN ERECTING A NON OPGW OVERHEAD EARTHWIRE.
10. POLE STEPS SHOULD ONLY BE INSTALLED ON POLES WHERE ACCESS FOR NORMAL MAINTENANCE VEHICLES CANNOT BE MAINTAINED FOR THE LIFE OF THE POLE. IF POLE STEPS ARE INSTALLED, THEY ARE TO COMPLY WITH THE REQUIREMENTS OF NETWORK STANDARD NS128.
11. REFER TO DESIGNER SAFETY REPORT D22/261971 FOR ATYPICAL HAZARDS ASSOCIATED WITH THIS STANDARD CONSTRUCTION.

8	STEP - POLE (SEE NOTE 10)	514084	A/R
7	OPGW - SPLICE BOX & COILED CABLE BRACKET, CONDUCTOR, MOUNTING ARRANGEMENT (USE WITH OPGW OHEW OPTIONS ONLY)	565743	1
6	EARTHWIRE - TERMINATION, OVERHEAD, MOUNTING, ARRANGEMENT -2B (SEE NOTES 6, 8 & 9)	519450	1
	OPGW - TERMINATION, CONDUCTOR, MOUNTING, ARRANGEMENT -2B (SEE NOTES 6, 8 & 9)	565747	
5	INSULATOR - LONGROD, 33KV, DUAL CONDUCTOR, POLYMERIC STRING, ARRANGEMENT -2 (SEE NOTES 4 & 8)	250120	3
	INSULATOR - LONGROD, 33KV, POLYMERIC STRING, ARRANGEMENT -2 (SEE NOTES 4 & 8)	158754	
4	CROSSARM - MOUNTING ARRANGEMENT -2a (GALVANISED STEEL OR COMPOSITE FIBRE CROSSARM) (SEE NOTES 5 & 7)	514176	1
3	FOOTING - CONCRETE POLE, ARRANGEMENT (SEE NOTE 1)	512331	1
2	EARTHING - CONCRETE/STEEL, SINGLE POLE, BUTT, ARRANGEMENT	520209	1
1	POLE - CONCRETE (AS REQUIRED)		1
ITEM	DESCRIPTION	DRG. No	QTY

ALL DIMENSIONS IN MILLIMETRES UNLESS NOTED OTHERWISE. DO NOT SCALE.

CAD DRAWING DO NOT MANUALLY AMEND	
A M E N D M E N T S	
DWN: GARY HUGHES	CHKD: GARRY CRAIG
DATE: 14/10/2013	AUSGRID BORDER APPLIED.
APP'D by: GLENN FORD	
DWN: P.R.	CHKD: P.J.
APP'D: G.F.	
DATE: 08/11/2022 MULTIPLE CROSSARM OPTION & FOUNDATION DETAILS ADDED. NOTES & MATERIAL LIST AMENDED. DUAL CONDUCTOR & OHEW OPTIONS ADDED.	

NETWORK STANDARD

145 NEWCASTLE RD WALLSEND,
NSW 2287

SCALE	1:25
DESIGNED	PHIL JONES
DRAWN	PATRICIA RIOS
CHECKED	PHIL JONES
APPROVED	STEPHEN CONNOR
DATE	20/12/2007
PROJECT NUMBER	STD
PROJTRAK NUMBER	-

STANDARD CONSTRUCTION			
33kV TERMINATION CONSTRUCTION			
WITH OVERHEAD EARTHWIRE			
4-10C/E			
SIZE	DRAWING No	SHEET	AMD
A3	174184	1	2